## ΜΛΝϽίκ

## DECLARATION OF PERFORMANCE No. PM/CFDM250/01/21/1

Unique identification code of	CFDM 250		
the product-type			
Products	Dampers – Fire dampers		
Intended use	Fire safety. To be used in conjunction with partitions to maintain fire		
	compartments in heating, ventilating and air conditioning installations.		
Technical documentation	Technical specifications TPM 152/21		
<ul> <li>product information, instruction</li> </ul>			
Manufacturer	MANDÍK, a.s.		
	Dobříšská 550, 26724 Hostomice, Czech Republic		
	ID 26718405, tel. +420 311 706 706		
	mandik@mandik.cz, www.mandik.com		
System of AVCP	System 1		
Harmonised standard	EN 15650:2010		
Notified body	Notified body No. 1391		
	PAVUS, a.s., Prosecká 412/74, 190 00 Praha 9 – Prosek		
Output documents of the	Certificate of Constancy of Performance No. 1391-CPR-2021/0075		
notified body	Assessment Report of Performance of Construction Product		
	No. P-1391-CPR-2021/0075		
	Products Intended use Technical documentation – product information, instruction for installation and maintenance, safety information Manufacturer System of AVCP Harmonised standard Notified body		

7a.	<b>Declared performances – fire resistance classification</b> Essential characteristics in accordance with EN 15650:2010, art. 4.1.1				
	eparating construction, ion of the damper	Installation type, installation system	Performance – class of fire resistance		
Solid ceiling construction – damper in the ceiling – ceiling thickness – min. 110 mm for concrete – min. 125 mm for aerated concrete		Mortar or gypsum <sup>1]</sup>	El 90 (h₀ i⇔o) S		

1] Refer to Technical documentation for the details of the installation type / installation system.

7b. Declared performances – o	Declared performances – other essential characteristics				
Essential characteristics	Requirements (provisions o the harmonised standard E 15650:2010)				
Nominal activation conditions/sen	sitivity: 4.2.1.2	Conforms			
<ul> <li>sensing element load bearing ca</li> </ul>	pacity 4.2.1.2.2	Conforms			
- sensing element response tempe	erature 4.2.1.2.3	Conforms			
Response delay (response time): – closure time	4.2.1.3	Conforms			
Operational reliability: – cycling	4.3.1, a)	0 cycles – conforms			
Durability of response delay:	4.2.1.2.2	Conforms			
<ul> <li>sensing element response to</li> </ul>	4.2.1.2.3				
temperature and load bearing cap	acity				
Durability of operational reliability – opening and closing cycle tests	: 4.3.3.2	NPD – no performance determined			

7c.	Declared performances – other characteristics		
Char	acteristics	Technical standard	Performance (lever or class) / Compliance with the requirements
Resis	tance against corrosion	EN 15650:2010, art. 4.2.2 EN 15650:2010, Annexe B	Conforms

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

In Hostomice, 2020-10-07

Marcel Mandík CEO

MANDÍK, a.s.

PM/CFDM250/01/21/1